

Description

- ▲ Available in 3 diameters; 1200mm, 1400mm and 1600mm.
- ▲ The standard unit comes with 11 treads plus a landing tread and can reach a floor height up to 2760mm. Heights of up to 3450mm can be achieved by using additional tread kits.
- ▲ Min. opening sizes are 1250mm x 1250mm (1200mm diameter stair), 1450mm x 1450mm (1400mm diameter stair) and 1650mm x 1650mm (1600mm diameter stair).
- ▲ The steel metalwork is available in Black or Silver Grey colour options.
- ▲ The 38mm solid beech treads (*clear varnished*) are available in either a natural or dark walnut colour option.
- ▲ The handrail is a black plastic (moplen) type and the balusters are 22mm steel (Black or Silver Grey colour options).
- ▲ The tread angle for the Gamia Wood is at 30° for all 3 diameter choices.
- ▲ Optional upper floor balustrade for the Gamia Wood is also available.
- ▲ In order to comply with building regs, we can supply riser bars these ensure that the distance between the treads does not exceed 100mm.

Wood finishes



Natural Walnut

Metal finishes



Black Silver grey



Black metalwork



Silver Grey metalwork

Gamia Wood Stair Heights

Staircase Height	No. of Risers	Tread Kits Required	Handrail Kits Required	Column Kits Required
2100 mm - 2300 mm	10	-	-	-
2310 mm - 2530 mm	11	-	-	-
2520 mm - 2760 mm	12	GAMIA WOOD STANDARD KIT		
2730 mm - 2990 mm	13	1	-	1 *
2940 mm - 3220 mm	14	2	1	1 *
3150 mm - 3450 mm	15	3	1	1 *

Height dimensions in the above chart are based on an individual rise from 210mm to 230mm.

Rises from 200 to 210mm & 230 to 240mm are possible with baluster adjustments made at the point of assembly.

* These Supplementary Column Kits (Centre Post) are required for the Gamia Wood Spiral Stair to achieve higher floor heights up to 3450mm